

CB TRANSPORTABLE SILOS

Model Number	Diameter (Metres)	Overall Height	Wheat Tonnes	Barley
CB12/3	3.66	4.93	27	23
CB12/4	3.66	5.74	34	29
CB12/5	3.66	6.55	41	35
CB12/6	3.66	7.36	47	40

PRICE AVAILABLE ON REQUEST

The silo comes complete with external wall ladder.

Standard Tubular 30° Cone Base Silo

- Height under valve .500mm
- Auger Length 45'



HL TRANSPORTABLE SILOS

Model Number	Diameter (Metres)	Overall Height	Wheat Tonnes	Barley	Height under valve	Auger length
HL12/3 - 30°	3.66	5.930	25	21	1.400	45
HL12/4 - 30°	3.66	6.740	32	27	1.400	45
HL12/5 - 30°	3.66	7.550	38	33	1.400	45
HL12/3 - 45°	3.66	5.900	27	23	.600	45
HL12/4 - 45°	3.66	6.740	34	29	.600	45
HL12/5 - 45°	3.66	7.550	40	35	.600	45
HL12/3 - 60°	3.66	7.000		28	.680	45
HL12/4 - 60°	3.66	7.800		34	.680	45
HL12/5 - 60°	3.66	8.500		40	.680	45

PRICE AVAILABLE ON REQUEST

Specification: Corrugated galvanised walls, galvanised roof c/w ladder, outside wall ladder, self opening lid, painted steel base on five legs at 2.0m spacings, cone bottom 30°, 45° & 60° c/w manhole.



PLEASE NOTE: All Capacities for Silos are approx. only, calculated at - .770kg per cubic metre for wheat, 653kg per cubic metre for barley which may vary dependant on moisture and compaction